


TELEPHONE CABLE SE XP AWG20 COPPER

ORSYTIXPAWG20RGSE



Construction



Conductor
Diameter

Copper
AWG 20

Insulation
Diameter

Solid PE
1.20 +/- 0.02 mm

Rip Cord

Outer Sheath
Color

PVC
Red RAL3000

Marking

SYT SE 1 PAIR AWG 20 ORSEANCABLES Eca RSYT60-XX WW/YY xxxxxM
Remark: x-number of pair; XX-Supplier code; WW-Week; YY-Year;
RSYT60-XX-DoP number

Thickness, Diameter & Colour code

REFERENCE	Dop Number	Thickness +/- 10% (mm)	Diameter +/- 10% (mm)
RSY-TELSE120PC	RSYT60-XX	0.4 / 0.6	3.7

Properties

Voltage Endurance: 300 V

Temperature Range: -10°C ~ + 70°C

Dielectric Strength : DC 1500V during 1 min.

Insulation Resistance : 1500 MΩ.Km

Conductor Resistance: 41 Ω/KM

Fire Retardant: According to CPR Eca

RoHS GUIDELINE

We operate according to the following standards

Control Item	Standard	Testing Method	Testing Equipment
Cadmium content (Cd)	<0.01%	EN1122	ICP-AES
Lead content (Pb)	<0.1%	EPA3050B	ICP-AES
Mercury content (Hg)	<0.1%	EPA3052	ICP-AES
Chromium (VI) content	<0.1%	EPA3060(UN-VIS)	ICP-AES
Polybrominated Biphenyls(PBB)	Forbidden	GC/MS	ICP-AES
Polybrominated Diphenyl Ether (PBDE)	Forbidden	GC/MS	ICP-AES

Cables with number of 1 pair :

Pair N	Wire 1	Wire 2
1	White	Red